

The MIMETIC is a medium payload industrial robot with a superior working range, advanced servo control technology, and an extremely rigid arm, significantly reducing cycle times and ensuring high productivity.

MIMETIC is a complete solution for medium payload class industrial robots to secure your future planning and production investment. From 20 kg up to 120 kg of fine load breakdown.

It is the perfect solution to ensure accuracy and production quality. Whether handling, machine loading/unloading, painting, stamping, palletizing, grinding, picking/packing, or assembly/distribution. In addition, you will have the freedom to choose the robot corresponding to your actual needs for greater efficiency and economic benefits.

All MIMETIC series are equipped with LIKEPRECISION technology, he ultra-precise RV Precision Gearbox, which enables the robot to take full advantage of its advantages even at high operating speeds.

Applications







Glazing
















Picking/Packing Stamping

SF20 - K1735 Wrist Load Curve Chart





SF20 - K1735 Load Range Curve Chart

SF20 - K1735 Data Overview


Model		SF20 - K1735
Structure		Vertically Articulated
Number of Axis		6
Radius		1735mm
Payload		20kg
Repeatability		±0.05mm
Drive Mode		AC Servo Motor
Maximum Speed	J1 J2 J3 J4 J5 J6	135°/s 135°/s 135°/s 300°/s 300°/s 500°/s
Range of Motion	J1 J2 J3 J4 J5 J6	±175° +68°/-150° +150°/-75° ±178° +135°/-125° ±720°
Allowable Moment	J4 J5 J6	42N·m 42N·m 23N·m
Allowable Inertia	J4 J5 J6	1.26kg·m² 1.26kg·m² 0.49kg·m²
Protection Rating		IP 65
Operating Conditions	Temp.	0-45°C
	Humidity	Below 95%RH
	Vibration	Below 4.9m/s ²
	Other	Eliminate Signal Noise
Base Size		370*370mm
Height		1563mm
Weight		206KG
Mounting Positions		Floor、Wall、Ceiling
Power Consumption		3.25kVA

SF20 - K1735 Range of Motion






SF20 - K1735 External & Installation Dimensions



A-Way Diagram (End Flange Mounting Dimensions)



B-Way Diagram (Base Mounting Dimensions)

